

PRODUCT DATA SHEET

FRICTIONLESS FOAM WASH

DESCRIPTION

Frictionless Foam Wash is a highly concentrated, strong alkaline frictionless foam cleaner with extraordinary cleaning and clinging capacity, that will remove even the most stubborn soiling. The product is recommended for cleaning cars, trucks, trailers and under bodies, earthmoving gear, agricultural equipment, etc. Suitable for stubborn grease, grime, and dirt.

CHEMICAL PROPERTIES

Sodium Hydroxide	<10%
Sodium laureth sulfate	<10%
Sodium Xylenesulphonate	<10%
L Glutamic acid	10-20%

METHOD OF USE

Using a foam cannon, apply a thin layer of foam over dry vehicle and allow to sit for 1 minute. Use a 3% mix for a foam injector and use at a 1:4 ratio when using a foam cannon. This is a guide and is dependent on the severity of the soiling, as well as the type of equipment being used.

Using a high-pressure machine begin cleaning from the bottom up, moving into fresh soap while you work. Rinse off excess soap from top to bottom once clean.

Do not use in direct sunlight and don't let the product dry completely, should this happen re-foam to reactivate the soap.

The product is safe on all paints, stainless steel, and chrome.
 Do not use on mirror polished aluminium as it may leave white streaks.

SAFETY PRECAUTIONS

SKIN	Wash with soap and water. Gloves are recommended.
EYES	Remove contact lenses. Flush with water or saline for 15min

KEEP OUT OF REACH OF CHILDREN

FOR MORE INFORMATION CONTACT 082 873 2688

responsible chemistry

Suppliers of Water Treatment programs and Systems
 Industrial and Domestic Chemicals
 & Bio Augmentation Products